

Supplier name:
Ningbo Sunpu Led Co.,Ltd.,

Acknowledgment number:

Product Acknowledgment

Customer Name:

Supply-side model:

Acknowledgment Effective Date:

Manufacturers		Client Confirm（Quality）		Client Confirm（R & D）	
Prepared		Qualified ☐		Qualified ☐	
		Unqualified ☐		Unqualified ☐	
Audit		Audit		Audit	
Approve		Approve		Approve	

（ After both sides confirmed the Acknowledgment qualified,must be signed and sealed ）

Supply-side Address: No 150.XinHui Road, Hi-Tech Park,Ningbo,china
Tel: 0574-87740939



COB-V2 series



Features:

- ✧ High brightness、high reliability、long life
- ✧ Light angle: 120°
- ✧ Typical color temperature: 3000K
- ✧ Ra : 90+
- ✧ In line with the EU ROHS standard

Product introduction

*Constant Voltage Drive

Works directly with constant voltage power, no need for complex current drivers. Simple, compatible, easy to install.

*Efficient COB Packaging

Low thermal resistance, fast heat dissipation, long lifespan—ideal for frequent use.

*High Brightness & Color Accuracy (Ra≥90)

Perfect for commercial, residential, and display lighting.


Contents

Outline dimensions	3
Circuit structure.....	3
Limit parameter	3
Photoelectric parameters	4
Typical curve	5
Chromaticity Coordinates Ranks.....	6
Reliability test and results.....	8
Packaging	9
Using and attention	10
Model naming rules.....	14



Part No.: **V2-30-3-N-4-7-19-12-A4-A**


Outline dimensions



NOTES:

- ✧ All dimensions are millimeter.
- ✧ Tolerance is $\pm 0.3\text{mm}$ unless otherwise noted.
- ✧ It is strongly recommended that the temperature of T_s (Welding plate) is not higher than 105°C .
- ✧ It is forbidden to store and use in the environment of sulfur and halogen elements.

Circuit structure



Limit parameter ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Test Condition	Value		Unit
			Min.	Max.	
DC Forward Current	I_F	----	----	533	mA
Peak Pulse Current	I_{peak}	Duty=1/10 1kHz	----	666	mA
Power Dissipation	P_d	----	----	13.3	W
LED Junction Temperature	T_J	----	----	125	$^\circ\text{C}$
Operating Temperature	T_{opr}	----	-40	+85	$^\circ\text{C}$
Storage Temperature	T_{str}	----	-40	+100	$^\circ\text{C}$
ESD Sensitivity	----	HBM	2000	----	V
Soldering Temperature	----	----	350 $^\circ\text{C}$ for 5 Seconds max		



Part No.: **V2-30-3-N-4-7-19-12-A4-A**

Photoelectric parameters (Ta = 25°C)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Forward Voltage	V _F	I _F = 500mA, V _F = 24V	--	24	--	V
DC Forward Current	I _F		450	500	533	mA
Luminous Flux	Φ _v		900	1050	--	lm
Color Temperature	CCT		2970	3045	3120	K
Color Rendering	R _a		90	--	--	
Color Rendering	R ₉		50	--	--	
Thermal Resistance	R _J		--	2	--	°C/W

Part No.: V2-30-3-N-4-7-19-12-A4-A

Typical curves:

Fig.1 Forward Current(mA) Vs Relative Forward Voltage(V)




Fig. 2 Forward Voltage Vs Relative Luminous Flux




Fig.3 Max Driving Forward Current Vs Temperature of Ts






Fig.4 Relative Luminous Flux Vs Temperature of Ts (VF=24V)



Part No.: V2-30-3-N-4-7-19-12-A4-A

Chromaticity Coordinates Ranks($I_F=500\text{mA}$, $V_F=24\text{V}$ $T_a=25^\circ\text{C}$)

ANSI 3000K 3step





Part No.: **V2-30-3-N-4-7-19-12-A4-A**

BIN	Luminous Flux (lm)	BIN	Luminous Flux (lm)
A	0-5	R2	3000-3500
B	5-10	S2	3500-4000
C	10-15	T2	4000-4500
D	15-20	U2	4500-5000
E	20-25	V2	5000-5500
F	25-30	W2	5500-6000
G	30-35	X2	6000-6500
H	35-40	Y2	6500-7000
J	40-50	Z2	7000-7500
K	50-60	A3	7500-8000
L	60-80	B3	8000-8500
M	80-100	C3	8500-9000
N	100-120	D3	9000-9500
P	120-140	E3	9500-10000
Q	140-160	F3	10000-10500
R	160-180	G3	10500-11000
S	180-200	H3	11000-11500
T	200-240	J3	11500-12000
U	240-280	K3	12000-12500
V	280-320	L3	12500-13000
W	320-360	M3	13000-13500
X	360-400	N3	13500-14000
Y	400-450	P3	14000-14500
Z	450-500	Q3	14500-15000
A2	500-600	R3	15000-15500
B2	600-700	S3	15500-16000
C2	700-800	T3	16000-16500
D2	800-900	U3	16500-17000
E2	900-1000	V3	17000-17500
F2	1000-1200	W3	17500-18000
G2	1200-1400	X3	18000-18500
H2	1400-1600	Y3	18500-19000
J2	1600-1800	Z3	19000-19500
K2	1800-2000	A4	19500-20000
L2	2000-2200	B4	20000-20500
M2	2200-2400	C4	20500-21000
N2	2400-2600	D4	21000-21500
P2	2600-2800	E4	21500-22000
Q2	2800-3000	F4	22000-22500



Part No.: **V2-30-3-N-4-7-19-12-A4-A**

Reliability Tests and Results

Test	Reference Standard	Test Conditions	Test Duration	Units Failed/T ested
High Temperature Storage	JEITA ED-4701 200 201	$T_A=100^{\circ}\text{C}$	1000hours	0/10
High Temperature Humidity Storage	JEITA ED-4701 100 103	$T_A=85^{\circ}\text{C}$ RH=85%	1000hours	0/10
Low Temperature Storage	JEITA ED-4701 200 202	$T_A=-40^{\circ}\text{C}$	1000hours	0/10
High Temperature Operating Life	JESD22-A108D	$TC=85^{\circ}\text{C}$ $I_F=500\text{mA}$, $V_F=24\text{V}$	1000hours	0/10
Electrostatic Discharges	JEITA ED-4701 300 304	HBM 2KV 3K Ω 100Pf 3pulses negative		0/10
Temperature Cycle *1	Sunpu-opto	-40°C (30min) $\sim$ (90s) $\sim$ 110°C (30min) $\sim$ (90s) -40°C	300cycles	0/10

NOTES:

* Measurements are performed after allowing the LEDs to return to room temperature

Failure Criteria

Items	Conditions	Failure Criteria
Forward Voltage (VF)	$I_F=500\text{mA}$, $V_F=24\text{V}$	>Initial value x 1.1
Luminous Flux (Φ_V)	$I_F=500\text{mA}$, $V_F=24\text{V}$	<Initial value x 0.7

Notes:

- ✧ Tolerance of measurements of the Forward Voltage is $\pm 2\%$
- ✧ Tolerance of measurements of the Luminous Flux is $\pm 10\%$
- ✧ Tolerance of measurements of the Color Rendering R_a is ± 2
- ✧ Chromaticity Coordinates (x,y) is measured with an accuracy of ± 0.01
- ✧ Ranking at $T_C=25^{\circ}\text{C}$




升谱光电
SUNPU

Ningbo Sunpu LED
Co., Ltd.

COB-V
SPECIFICATION

Part No.: V2-30-3-N-4-7-19-12-A4-A

Packaging



40 pcs/tray (5*8=40pcs)


Label instructions

升谱光电 SUNPU		QR Code	
品号:	110301001445		
品名:	L16-604H0312-1800SC		
批号:	SFSP12-2409110037		
色温:	W60IV		
显指:	Ra80	光通量:	K2
客户料号:			
Qty:	0.2 KPCS	QC:	
日期:	2024-09-25		

Part No.: V2-30-3-N-4-7-19-12-A4-A

Using and attention

1、 Application Guide




2、 Soldering

COB light source device is a very fragile encapsulation device. Careless in the process of soldering operation will cause the damage of the products easily and even lead to death lamp. client should be cautious. In the process of soldering iron or other welding equipment to heat up, please don't use hand or other items to put any pressure on the surface of a product, please avoid iron touch within white rubber dam. because under the white dam it is likely to be the gold thread connection with substrate. If it is extruded by any external things, it is likely cause that connections between gold wire and substrate loose or fall off leading to product stroboscopic at work or death lamp. soldering temperature shall not be higher than 350 °C and the time shall not be more than 3 seconds and the number less than 2 times. When the soldering operation is completed , it is necessary that the product is cooled to room temperature, then washed again, and other operations.

Part No.: V2-30-3-N-4-7-19-12-A4-A

3、 Cleaning

After soldering it is recommended that client should use alcohol to clean, The specific method is that Using tweezers clamping alcohol cotton ball in the source surface lightly wipe back and forth to clean, Prohibit the forceps tip injury to the source surface .Before using other similar solvent cleaning, please make sure that to use the solvent will not damage the product packaging materials such as silica gel and phosphor etc.



4、 Storage

Part No.: V2-30-3-N-4-7-19-12-A4-A

This product use sealed moisture-proof anti-static bag packaging, storage method is as follows:

- ✧ Opened before, the product must be stored in room temperature and humidity environment is not higher than 70% RH.
- ✧ Once opened, the product can be stored in room temperature and humidity is not higher than 70% RH of the environment in a week, please use in the period of time.

If not timely installation after opening, Should be stored in dry cabinet temperature and humidity not higher than 10%RH .

5、 Static electricity

Static and surge can cause product characteristics change, such as forward voltage to reduce, if severe cases may even damage the product. So When in use effective anti-static measures must be taken. All related equipment and machines should be properly grounded, at the same time must take other measures to prevent static and surge. Use anti-static bracelet, anti-static MATS, anti-static overalls, work shoes, gloves, anti-static container, are effective measures to prevent static and surge.



6、 Driving and cooling scheme

In the design of driving, by the current cannot exceed a maximum value specified products. Over voltage, over current pulses generated at the moment of the power switch or reverse voltage pulse may cause product damage and even death light. Therefore it is recommended that choose drive power selection of high stability. Because the heat this for product is concentrated, It should be the choice of high

Part No.: V2-30-3-N-4-7-19-12-A4-A

thermal conductivity thermal grease or conductive adhesive and Evenly coated on the light back. There can be no gap between substrate and radiator.

**7、 Halogen**

Halogen will damage the product, affecting device performance. Reference standards such as IEC, IPC and JPCA - ES, customers to use material, each kind of halogen content shall not be higher than 900 PPM, halogen sum shall not be higher than 1500 PPM.

- ✧ Halogen include: F, Cl, Br, I
- ✧ Common containing halogen material: white oil, pouring sealant, sealant, line insulation casing, etc.

8、 External force

Packaging adhesive products (including the white dam colloid) is fragile , when in use should pay attention to the following points:

- ✧ Do not use hard, sharp objects scratch, wipe the packaging adhesive part.
- ✧ Do not hand take products, avoid pollution package silica surface, and influence its optical properties.
- ✧ It should be noted that when using tweezers clip excessive pressure may damage , packaging silica gel , for example, damage, scratches, peeling, serious deformation and die lamp.

Part No.: V2-30-3-N-4-7-19-12-A4-A

✧ Products dropped, the product may lead to deformation.

